

**CEM-N001 ELECTRICALLY CONDUCTIVE
NICKEL FILLED SILICONE ELASTOMER****Product overview**

CEM-N001 is an electrically conductive composite material comprising of silicone elastomer and nickel particles. It is formulated for the production of sheet, flat gaskets and custom mouldings that offer a combined high level of EMI shielding and environmental sealing over a wide temperature range. The silicone elastomer base provides excellent resistance to extremes of temperature and long term ageing.

CEM-N001 also exhibits good galvanic (electro-chemical) stability when used in combination with aluminium alloys, particularly in humid or damp environments.

Cured Properties	
Colour	Dark grey
Density	4.5 gcm ⁻³
Hardness Range	30-80 Shore A Standard 70 Shore A
Volume resistivity	<0.2Ω.cm
Tensile strength	1.2MPa
Elongation	200%
Compression set – 72 hours at 100°C	20%
Service temperature range	-55°C to 150°C

**CEM-N001 ELECTRICALLY CONDUCTIVE
NICKEL FILLED SILICONE ELASTOMER****Shielding Effectiveness**

10kHz (H field)	65dB
100kHz (H field)	70dB
1MHz (H field)	>100
20MHz (E field)	>100dB
100MHz (E field)	>110dB
400MHz (Plane wave)	>110dB
1GHz (Plane wave)	>100dB
10GHz (Plane wave)	>100dB

Available forms

The equivalent material type (CEM-N001) is also available in the form of sheets, flat gaskets and custom moulded components. Gaskets and the sheet material can be supplied with a self adhesive backing to assist installation / assembly.

Shielding Solutions Ltd
410 Avenue West
Skyline 120
Great Notley
Essex
CM77 7AA

Tel: 01376 330033

Fax:01376 339163

Web: www.shielding-solutions.com

SSL/TDS/72 ISS 1

21/08/2013